



**NOTES:**

- ① DRIVE SIGN POST ANCHOR INTO GROUND APPROXIMATELY 1.0 m (3'). LEAVE ONE HOLE EXPOSED ABOVE GROUND FOR RIVET CONNECTION.
- ② DRIVE IN ANCHOR SLEEVE WHICH IS ONE SIZE LARGER THAN POST ANCHOR AND 455 mm (18") LONG.
- ③ INSERT SIGN POST AND FASTEN IN PLACE.
- ④ 2.1 m (7') MINIMUM CLEARANCE TO BOTTOM OF THE LOWEST SIGN.

**CITY OF PASADENA - PUBLIC WORKS & TRANSPORTATION DEPARTMENT**

DRAWN BY: *GP*  
 GLENN PENARUBIA

CHECKED BY:  
 JOSE LOERA

SUBMITTED BY: *NB*  
 NORMAN BACULINAO

**NEW SIGN POST INSTALLATION**

APPROVED BY:  
*Bahma Jansen*

7/7/03  
 DATE

TRANSPORTATION ADMINISTRATOR RTE NO. 1520 EXPIRES JUNE 30, 2005

REVISION: 1 UNITS: DUAL

STANDARD PLAN:  
**S-715**

SHEET 1 OF 1  
 S715-1-REV1.DWG 7/8/03