



SECTION A-A

NOTES:

- ① CONSOLIDATED BACKFILL OR CONCRETE SIDEWALK, SLOPE TO DRAIN.
- ② CONCRETE MAY BE PREMIXED, SACKED CONCRETE OR FIELD PROPORTIONED CEMENT AND AGGREGATE WITH WATER ADDED AND MIXING OCCURRING ON THE JOB SITE. 2% CALCIUM CHLORIDE (BY WEIGHT OF CEMENT) MAY BE ADDED TO PRODUCE A QUICKSET CONCRETE. CONCRETE SHALL COMPLY WITH "STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION," LATEST EDITION.

CITY OF PASADENA - PUBLIC WORKS & TRANSPORTATION DEPARTMENT

DRAWN BY:
Maggie Mojica
MAGGIE MOJICA

CHECKED BY: *AJ*
ADOLFO VARGAS

SUBMITTED BY *CH*
CHRISTINE HERNANDEZ

**STOP SIGN
 AND POST REPLACEMENT**

APPROVED BY:
Bahar Saberi
TRANSPORTATION ADMINISTRATOR

7-23-01
 DATE

REVISION: 1
 UNITS: DUAL

STANDARD PLAN:
S-717

SHEET 1 OF 1
 5717-1-REV1.DWG 7/25/01